Theatre diffuser

CCP

1

2

4

7

8

10

12

13

15

16

17

18



Description

CCP is a circular displacement diffuser for installation under seats in theatres, auditoriums, etc. This diffuser is suitable for installation in a pressure chamber. It has a fixed resistance that ensures even distribution of the air. The diffuser can be adapted to the correct air volume and pressure, specified according to the actual conditions.

- It has built-in resistance that ensures even distribution over the diffuser
- The diffuser can be supplied with a specified pressure setting
- The diffuser is available in other dimensions

Maintenance

The front plate of the diffuser can be removed to enable cleaning of the internal components. The visible parts of the diffuser can be wiped with a damp cloth.

Materials and finish

Diffuser: Galvanised steel
Front plate: 1 mm galvanised steel
Standard finish: Powder-coated


Standard colour: RAL 7040 - grey, gloss 30 RAL 9010 - white, gloss 30

The diffuser is available in other colours. Please contact Lindab's sales department for further information.

Order code


| Product | C | СР | а | bbb |
|---------|---|-------------|---|-----|
| Type | |] | | |
| Colour | RAL 7040 - grey RAL 9010 - white Special colour | 0 1 2 | | |
| Size | | | | |

Dimensions




| | ØA | ØD ₁ | Weight | |
|------|-----|-----------------|--------|--|
| Size | mm | mm | kg | |
| 100 | 140 | 100 | 0,70 | |
| 125 | 160 | 125 | 0,90 | |

Pressure, sound level



| Size | 63 | 125 | 250 | 500 | 1K | 2K | 4K | 8K |
|------|----|-----|-----|-----|----|-----|-----|-----|
| 100 | | | | | | | -13 | |
| 125 | 3 | -7 | -5 | 0 | -5 | -10 | -15 | -27 |

Near zone



The speed is measured 0.5 m from the diffuser.